# CRC

# SAFETY DATA SHEET

# 1. Identification

Product identifier Brakleen® Pro Series Non Chlorinated Low VOC

Other means of identification

Product Code No. 05084PS (Item# 1008010)

**Recommended use Brake cleaner Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

**Telephone** 

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

# 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Compressed gas
Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1
Hazardous to the aquatic environment, acute Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

OSHA defined hazards Not classified.

Label elements

**Health hazards** 



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Very toxic to aquatic life. Very toxic to aquatic life with long lasting

effects.

Material name: Brakleen® Pro Series Non Chlorinated Low VOC

No. 05084PS (Item# 1008010) Version #: 02 Revision date: 12-29-2017 Issue date: 04-17-2017

## **Precautionary statement**

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this

label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wear eye

protection/face protection. Wear protective gloves. Wash thoroughly after handling. Avoid release

to the environment.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

> with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice/attention. Collect spillage.

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to **Storage** 

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Dispose of contents/container in accordance with local/regional/national regulations. **Disposal** 

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
acetone		67-64-1	50 - 60
n-heptane		142-82-5	10 - 20
3-methylhexane		589-34-4	5 - 10
carbon dioxide		124-38-9	5 - 10
2-methylhexane		591-76-4	3 - 5
heptane, branched, cyclic and linear		426260-76-6	3 - 5
methylcyclohexane		108-87-2	3 - 5
naphtha (petroleum), hydrotreated light	1	64742-49-0	3 - 5
solvent naphtha (petroleum), light aliph.		64742-89-8	3 - 5
3-ethylpentane		617-78-7	1 - 3
3,3-dimethylpentane		562-49-2	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

treatment needed

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical Skin contact

advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Most important Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, symptoms/effects, acute and

redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. delayed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Indication of immediate Symptoms may be delayed. medical attention and special

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Material name: Brakleen® Pro Series Non Chlorinated Low VOC

No. 05084PS (Item# 1008010) Version #: 02 Revision date: 12-29-2017 Issue date: 04-17-2017

## 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions General fire hazards

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

Precautions for safe handling

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place.

# 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Components	Type	Value
acetone (CAS 67-64-1)	PEL	2400 mg/m3
		1000 ppm
carbon dioxide (CAS	PEL	9000 mg/m3
124-38-9)		•
		5000 ppm
methylcyclohexane (CAS	PEL	2000 mg/m3
108-87-2)		
		500 ppm
naphtha (petroleum),	PEL	400 mg/m3
hydrotreated light (CAS		
64742-49-0)		100 nnm
n hantana (CAS 142 92 5)	DEL	100 ppm
n-heptane (CAS 142-82-5)	PEL	2000 mg/m3
a a le ca matema a ma la tila a	DEL	500 ppm
solvent naphtha (petroleum), light aliph.	PEL	400 mg/m3
(CAS 64742-89-8)		
(6/18/04/42/05/0)		100 ppm
IIO ACCIII Thurshald Lineit Value	_	. 55 рр
US. ACGIH Threshold Limit Values		Value
Components	Туре	Value
2-methylhexane (CAS	STEL	500 ppm
591-76-4)		
	TWA	400 ppm
3,3-dimethylpentane (CAS	STEL	500 ppm
562-49-2)		
	TWA	400 ppm
3-ethylpentane (CAS	STEL	500 ppm
617-78-7)	T)A/A	400 mmm
2 the the second (CAC	TWA	400 ppm
3-methylhexane (CAS 589-34-4)	STEL	500 ppm
309-34-4)	TWA	400 ppm
acetone (CAS 67-64-1)	STEL	500 ppm
acetone (CAS 07-04-1)	TWA	250 ppm
carbon dioxide (CAS	STEL	30000 ppm
124-38-9)	SILL	30000 ррш
121 00 0)	TWA	5000 ppm
methylcyclohexane (CAS	STEL	500 ppm
108-87-2)	0.22	occ pp
,	TWA	400 ppm
n-heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
US. NIOSH: Pocket Guide to Chem	nical Hazarde	
Components	Туре	Value
acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
carbon dioxide (CAS	STEL	54000 mg/m3
124-38-9)		20000
	T\A/A	30000 ppm
	TWA	9000 mg/m3
	T)A/A	5000 ppm
methylcyclohexane (CAS	TWA	1600 mg/m3
108-87-2)		400 nnm
nanhtha (natralaum)	T\A/A	400 ppm
naphtha (petroleum), hydrotreated light (CAS	TWA	400 mg/m3
64742-49-0)		
5 1 <u>2</u> 10 0)		100 ppm
n-heptane (CAS 142-82-5)	Ceiling	1800 mg/m3
	Coming	1000 mg/mo

# **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	
		440 ppm	
	TWA	350 mg/m3	
		85 ppm	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	400 mg/m3	
,		100 ppm	

## **Biological limit values**

ACGIH Biological Exposure Indices
-----------------------------------

Components	Value	Determinant	Specimen	Sampling Time
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene. Polyvinyl alcohol (PVA). Suitable gloves can be

recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

## **Appearance**

**Physical state** Liquid. **Form** Aerosol. Color Colorless. Solvent. Odor **Odor threshold** Not available. Not available.

-195.9 °F (-126.6 °C) estimated Melting point/freezing point Initial boiling point and boiling 132.9 °F (56.1 °C) estimated

range

Flash point 0 °F (-17.8 °C) Tag Closed Cup

Fast. **Evaporation rate** 

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits 1.1 % estimated

Flammability limit - lower

(%)

Flammability limit - upper

12.8 % estimated

(%)

4726.4 hPa estimated Vapor pressure

Vapor density > 1 (air = 1)Relative density 0.81 estimated

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available. (n-octanol/water)

539.6 °F (282 °C) estimated **Auto-ignition temperature** 

Not available. **Decomposition temperature** 91.6 % estimated Percent volatile

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** 

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Heat, flames and sparks. Contact with incompatible materials. Conditions to avoid

Acids. Strong oxidizing agents. Aluminum. Incompatible materials

Hazardous decomposition

products

Carbon oxides.

## 11. Toxicological information

# Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Causes skin irritation. Skin contact

Causes serious eye irritation. Eye contact

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

# Information on toxicological effects

May be fatal if swallowed and enters airways. **Acute toxicity** 

Components	Species	Test Results		
3-methylhexane (CAS 589-34-4)				
<u>Acute</u>				
Dermal				
LD50	Rabbit	> 2000 mg/kg		
Oral				
LD50	Rat	> 2000 mg/kg		
acetone (CAS 67-64-1)				
<u>Acute</u>				
Dermal				
LD50	Rabbit	20000 mg/kg		
Oral				
LD50	Rat	5800 mg/kg		
heptane, branched, cyclic and linear (CAS 426260-76-6)				
<u>Acute</u>				
Dermal				
LD50	Rabbit	> 2000 mg/kg		
Inhalation				
LC50	Rat	> 60 mg/l, 4 hours		

Components Species Test Results

Oral

LD50 Rat > 5000 mg/kg

methylcyclohexane (CAS 108-87-2)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

n-heptane (CAS 142-82-5)

Acute Dermal

LD50 Rabbit 3000 mg/kg

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting,

may cause chemical pneumonia, pulmonary injury or death.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Components		Species	Test Results
acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Components Species Test Results

heptane, branched, cyclic and linear (CAS 426260-76-6)

**Aquatic** 

Acute

Crustacea EC50 Water flea (Daphnia magna) 1.5 mg/l, 48 hours

methylcyclohexane (CAS 108-87-2)

Aquatic

Fish LC50 Striped bass (Morone saxatilis) 5.8 mg/l, 96 hours

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Aquatic

Acute

 Crustacea
 EC50
 Daphnia
 1 - 10 mg/l, 48 hours

 Fish
 LC50
 Fish
 1 - 10 mg/l, 96 hours

n-heptane (CAS 142-82-5)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) 1.5 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 2.1 - 2.98 mg/l, 96 hours

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

**Aquatic** 

Fish LC50 Rainbow trout, donaldson trout 8.8 mg/l, 96 hours

(Oncorhynchus mykiss)

8.8 mg/l, 96 hours

Acute

Crustacea EC50 Water flea (Daphnia magna) 1.5 mg/l, 48 hours

Persistence and degradability No data is available on the degradability of this product.

#### Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

acetone -0.24 methylcyclohexane 3.61 n-heptane 4.66

**Bioconcentration factor (BCF)** 

naphtha (petroleum), hydrotreated light 10 - 25000

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

# 13. Disposal considerations

**Disposal instructions** This material and its container must be disposed of as hazardous waste. Collect and reclaim or

dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not

puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

# 14. Transport information

DOT

UN number UN1950

**UN proper shipping name** Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk -

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

2.1 Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** N82 Packaging exceptions 306 Packaging non bulk 304 None Packaging bulk

**IATA** 

**UN** number UN1950

Aerosols, flammable, Limited Quantity **UN proper shipping name** 

Transport hazard class(es)

2.1 Class Subsidiary risk

Packing group Not applicable.

**ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

**IMDG** 

**UN** number

**UN** proper shipping name AEROSOLS, Limited Quantity

Transport hazard class(es) 2 Class Subsidiary risk

Packing group Not applicable.

**Environmental hazards** 

No. Marine pollutant F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

3,3-dimethylpentane (CAS 562-49-2) Listed. acetone (CAS 67-64-1) Listed.

**CERCLA Hazardous Substances: Reportable quantity** 

3,3-dimethylpentane (CAS 562-49-2) 100 LBS 5000 LBS acetone (CAS 67-64-1)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

# Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number** 

acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

acetone (CAS 67-64-1) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

acetone (CAS 67-64-1) Low priority

Not regulated. Food and Drug

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Gas under pressure categories Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

# **US** state regulations

#### US. New Jersey Worker and Community Right-to-Know Act

3-methylhexane (CAS 589-34-4)

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

## **US. Massachusetts RTK - Substance List**

2-methylhexane (CAS 591-76-4)

3-methylhexane (CAS 589-34-4)

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

## US. Pennsylvania Worker and Community Right-to-Know Law

2-methylhexane (CAS 591-76-4)

3,3-dimethylpentane (CAS 562-49-2)

3-methylhexane (CAS 589-34-4)

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

#### US. Rhode Island RTK

acetone (CAS 67-64-1)

carbon dioxide (CAS 124-38-9)

methylcyclohexane (CAS 108-87-2)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

n-heptane (CAS 142-82-5)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Material name: Brakleen® Pro Series Non Chlorinated Low VOC

SDS US



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 benzene (CAS 71-43-2) Listed: February 27, 1987 cumene (CAS 98-82-8) Listed: April 6, 2010 ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 naphthalene (CAS 91-20-3) Listed: April 19, 2002

#### California Proposition 65 - CRT: Listed date/Developmental toxin

benzene (CAS 71-43-2) Listed: December 26, 1997 toluene (CAS 108-88-3) Listed: January 1, 1991

## California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2) Listed: December 26, 1997

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

acetone (CAS 67-64-1)

naphtha (petroleum), hydrotreated light (CAS 64742-49-0) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

## Volatile organic compounds (VOC) regulations

#### **EPA**

VOC content (40 CFR 40.5 %

51.100(s))

**Consumer products** 

(40 CFR 59, Subpt. C)

Not regulated

Inventory name

#### State

This product is regulated as a Brake Cleaner. This product is not compliant to be sold for use in Consumer products

California, Delaware, Maryland, New Hampshire, and the following counties in Utah: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber. This product is compliant in all other states.

40.5 % VOC content (CA) 40.5 % VOC content (OTC)

#### **International Inventories**

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Taiwan Taiwan Toxic Chemical Substances (TCS) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

## 16. Other information, including date of preparation or last revision

Issue date 04-17-2017 **Revision date** 12-29-2017 Allison Yoon Prepared by

On inventory (yes/no)\*

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Version # 02

Further information CRC # 942A/1002959

HMIS® ratings Health: 2

Flammability: 4 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 2

Flammability: 4 Instability: 0

**NFPA** ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

**Revision information** 

Product and Company Identification: Product Codes

Hazard(s) identification: Prevention

Handling and storage: Precautions for safe handling Physical & Chemical Properties: Multiple Properties Physical and chemical properties: Oxidizing properties Physical and chemical properties: Explosive properties

Disposal considerations: Disposal instructions
Disposal considerations: Hazardous waste code
Regulatory information: California Prop 65
Regulatory information: Consumer products

Other information, including date of preparation or last revision: Disclaimer

Other information, including date of preparation or last revision: Further information

Material name: Brakleen® Pro Series Non Chlorinated Low VOC

No. 05084PS (Item# 1008010) Version #: 02 Revision date: 12-29-2017 Issue date: 04-17-2017