



SAFETY DATA SHEET

Issuing Date 12-Jan-2016

Revision Date 28-Feb-2018

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Electro Contact Cleaner

Other means of identification

Product Code(s) EC-11

UN-Number UN1950

Synonyms Electro Contact Cleaner

Recommended use of the chemical and restrictions on use

Recommended Use An instant solvent and cleaner. Electro Contact Cleaner quickly removes grease, dust, oxidation and other contaminants from precision electronic instruments. Restores and maintains the original efficiency of all electronic instruments, eliminating noise caused by dust and dirt. Suggested Application: Alternators, distributors, regulators, relays, switches, contacts, timers, and buss bars.

Uses advised against No information available

Supplier's details

Supplier Address

AGS Company
P.O. Box 729
Muskegon, MI
49443
TEL: 800-253-0403

Emergency telephone number

Emergency Telephone Number 800-255-3924

2. HAZARDS IDENTIFICATION


Classification

This product is considered hazardous by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Reproductive Toxicity	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Aspiration Toxicity	Category 1

Flammable aerosols	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements**Emergency Overview**

Signal Word	Danger
Hazard Statements	
<ul style="list-style-type: none"> • Causes skin irritation • Causes serious eye irritation • May cause genetic defects • Suspected of damaging fertility or the unborn child • May cause drowsiness or dizziness • May be fatal if swallowed and enters airways • • Extremely flammable aerosol • Contains gas under pressure; may explode if heated 	
	
Appearance Colorless.	Physical State Aerosol.
	Odor Alcohol.

Precautionary Statements**Prevention**

- Wash face, hands and any exposed skin thoroughly after handling.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- Specific treatment (see supplemental instructions on the administration of antidotes on this label)
- If exposed or concerned: Get medical attention/advice

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
- Protect from sunlight

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable.

Other information

Toxic to aquatic life with long lasting effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

Electro Contact Cleaner

Chemical Name	CAS-No	Weight %	Trade secret
Naphtha	8030-30-6	40-70	*
2-Methylpentane	107-83-5	30-60	*
Propane	74-98-6	10-30	*
Isopropyl alcohol	67-63-0	10-30	*
Butane	106-97-8	7-13	*
Hexane	110-54-3	1-5	*

**The exact percentage (concentration) of composition has been withheld as a trade secret.*

4. FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off with warm water and soap. If symptoms persist, call a physician. Wash contaminated clothing before reuse.
Inhalation	Move to fresh air.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Rinse mouth.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use: Carbon dioxide (CO₂). Dry chemical. Foam.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Flammable. Pressurized container: Do not pierce or burn, even after use. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Explosion Data

Sensitivity to Mechanical Impact	Yes.
Sensitivity to Static Discharge	Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Contents under pressure. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

Environmental Precautions

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment

A vapor suppressing foam may be used to reduce vapors.

Methods for Cleaning Up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Non-sparking tools should be used. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Use only in an area containing flame proof equipment. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Contents under pressure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid breathing vapors. Remove and wash contaminated clothing before re-use.

Conditions for safe storage, including any incompatibilities

Storage

Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed in a dry and well-ventilated place. Contents of a container may be under pressure and may release dangerous aerosol vapors when opened.

Incompatible Products

Strong acids. Strong bases. Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Naphtha 8030-30-6	-	TWA: 100 ppm TWA: 400 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 400 mg/m ³	IDLH: 1000 ppm TWA: 100 ppm TWA: 400 mg/m ³
2-Methylpentane 107-83-5	STEL: 1000 ppm TWA: 500 ppm	(vacated) TWA: 500 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 1000 ppm (vacated) STEL: 3600 mg/m ³	Ceiling: 510 ppm 15 min Ceiling: 1800 mg/m ³ 15 min TWA: 100 ppm TWA: 350 mg/m ³
Naphtha, petroleum, hydrotreated light 64742-49-0	-	(vacated) TWA: 400 ppm (vacated) TWA: 1600 mg/m ³	IDLH: 1100 ppm Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³
Butane 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m ³
Hexane 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³ (vacated) STEL: 1000 ppm (vacated) STEL: 3600 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection
Skin and Body Protection
Respiratory Protection

Safety glasses with side-shields.
Wear protective gloves/clothing.
If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Aerosol. **Appearance** Colorless.
Odor Alcohol. **Odor Threshold** No information available.

Property	Values	Remarks/ - Method
pH	No data available	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	No data available	None known
Flash Point	No data available	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known

Flammability Limits in Air

upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known
Vapor Density	No data available	None known
Specific Gravity	0.62-0.78	None known
Water Solubility	15%	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Extremely flammable aerosol.

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%) 100

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Fire Hazard Heating may cause an explosion Keep away from heat and sources of ignition.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information****Inhalation**

There is no data available for this product

Aerosol expected to be irritating based on components May cause drowsiness and dizziness based on components. Avoid breathing vapors or mists.

Eye Contact

Expected to be an irritant based on components

Skin Contact

Expected to be an irritant based on components

Ingestion

Potential for aspiration if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available
Mutagenic Effects May cause genetic defects.
Carcinogenicity Contains no ingredients above reportable quantities listed as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropyl alcohol		Group 3		X

Legend:

IARC: (International Agency for Research on Cancer)
 Group 3 - Not Classifiable as to its Carcinogenicity to Humans

Reproductive Toxicity Suspected of damaging fertility or the unborn child.
STOT - single exposure May cause drowsiness or dizziness
STOT - repeated exposure No information available
Aspiration Hazard No information available.

Numerical measures of toxicity - Product**Unknown acute toxicity**

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 6443 mg/kg; Acute toxicity estimate
LD50 Dermal 46043 mg/kg; Acute toxicity estimate
Inhalation
gas 1099665
Vapor 5638.9 mg/L; Acute toxicity estimate

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Naphtha 8030-30-6	EC50 72 h: = 4700 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 9.2 mg/L static (Lepomis macrochirus)		
Naphtha, petroleum, hydrotreated light 64742-49-0		LC50 96 h: = 258 mg/L static (Salmo gairdneri)		EC50 48 h: < 0.26 mg/L Static (Daphnia magna) LC50 96 h: = 2.6 mg/L (Chaetogammarus marinus) EC50 24 h: = 36 mg/L (Daphnia magna)
Isopropyl alcohol 67-63-0	EC50 72 h: > 1000 mg/L (Desmodesmus subspicatus) EC50 96 h: > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 11130 mg/L static (Pimephales promelas) LC50 96 h: = 9640 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1400000 µg/L (Lepomis macrochirus)		EC50 48 h: = 13299 mg/L (Daphnia magna)
Hexane 110-54-3		LC50 96 h: 2.1 - 2.98 mg/L flow-through (Pimephales promelas)		EC50 24 h: > 1000 mg/L (Daphnia magna)

Persistence and Degradability No information available

Bioaccumulation

Chemical Name	Log Pow
Propane	2.3
Isopropyl alcohol	0.05
Butane	2.89

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of contents/container in accordance with local regulation This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT

UN-Number UN1950
Proper shipping name AEROSOLS, FLAMMABLE
Hazard Class 2.1
Description UN1950, Aerosols, flammable, (each not exceeding 1 L capacity), 2.1, Marine Pollutant
Emergency Response Guide Number 126

ICAO

UN-Number UN1950
Proper shipping name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

IATA

UN-Number UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
ERG Code 10L
Description UN1950, Aerosols, flammable, 2.1

IMDG/IMO

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2
Subsidiary Class See SP63
EmS No. F-D, S-U
Description UN1950, Aerosols, 2.1 (See SP63), (12°C c.c.), Marine Pollutant

15. REGULATORY INFORMATION

International Inventories

TSCA Contact supplier for inventory compliance status
DSL/NDL Contact supplier for inventory compliance status

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List**U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Hexane	110-54-3	3	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Hexane	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Hexane	110-54-3	X

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Naphtha	X	X	X		
2-Methylpentane	X	X	X		
Naphtha, petroleum, hydrotreated light	X	X	X		
Propane	X	X	X	-	X
Isopropyl alcohol	X	X	X		X
Butane	X	X	X		X
Hexane	X	X	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 4	Instability 2	Physical and Chemical Hazards -
HMIS	Health Hazard 2	Flammability 4	Physical Hazard 2	Personal Protection X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 12-Jan-2016

Revision Date	28-Feb-2018
Revision Note	Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet