

# Material Safety Data Sheet

May be used to comply with  
OSHA's Hazard Communication Standard  
29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

# U.S. Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072



Forms Published by WindowChem (707)864-0846

IDENTITY (As Used on Label and List)

**KG TYPE VINYL COATED FABRICS**

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

## Section I

Manufacturer's Name

**HAARTZ CORPORATION**

Emergency Telephone Number

**(978) 264 2600**

Address (Number, Street, City, State, and ZIP Code)

**87 HAYWARD ROAD**

Telephone Number for Information

**(978) 264 2600**

**ACTON, MA 01720-3000**

Date Prepared

7/9/2008

Signature of Preparer (optional)

## Section IIA - Ingredients/Identity Information

	% (optional)
POLYESTER COTTON FABRIC	10 - 20 %
FLEXIBLE POLYVINYL CHLORIDE COMPOUND	80 - 90 %

## Section IIB - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
ANTIMONY OXIDE CAS#1309-64-4				

## Section III - Physical/Chemical Characteristics

Boiling Point 10 MM Hg	256 °C	Specific Gravity (H2O = 1)	> 1.0
Vapor Pressure (mm Hg) 200 °C	0.3 mm Hg	Melting Point	> 85 °C.
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	NA

Solubility in Water

20°C < 0.01 % by weight plasticizer portion only

Appearance and Odor

Plastic coated foam/mild phthalate odor

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) >300° C. (ASTM D-1929)	Flammable Limits N/A	LEL N/A	UEL N/A
---	-------------------------	------------	------------

Extinguishing Media

Carbon Dioxide, Foam, Dry Chemical, Water Fog

Special Firefighting Procedures

Fire fighters and other persons subject to products of combustion should wear

self-contained breathing apparatus

Unusual Fire and Explosion Hazards

Not Known

**Section V - Reactivity Data**

Stability	Unstable		Conditions to Avoid Prolonged exposure to heat, avoid contact with ignition
	Stable	X	sources and strong oxidation

Incompatibility (Materials to Avoid) Strong Oxidizers

Hazardous Decomposition or Byproducts Carbon Monoxide, Carbon dioxide, Hydrogen chloride gas

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

**Section VI - Health Hazard Data**

Route(s) of Entry:	Inhalation? No	Skin? No	Ingestion? Unlikely
--------------------	-------------------	-------------	------------------------

Health Hazards (Acute and Chronic) Exposure to vapors from molten material may cause eye and respiratory track irritation

Carcinogenicity: None Know	NTP? No	IARC Monographs? No	OSHA Regulated? No
-------------------------------	------------	------------------------	-----------------------

Signs and Symptoms of Exposure None Known

Medical Conditions None Known

Emergency and First Aid Procedure  
Eyes: Flush with Water. Skin: Wash with soap and water.

Inhalation: Remove to fresh air, Seek medical attention

**Section VII - Precautions for Safe Handling and Use**

Steps to be Taken in Case Material is Released or Spilled Reroll, sweep small scraps

Waste Disposal Method Landfill in accordance with local, state and federal regulations

Precautions to be Taken in Handling and Storage Keep away from heat, sparks, flame. Store in a clean dry place

Store at temperatures below 55 oC

Other Precautions Not Determined

**Section VIII - Control Measures**

Respiratory Protection (Specify Type) No special protection for normal use

Ventilation	Local Exhaust	Local exhaust around processing is recommended	Special N/A
	Mechanical (General)	N/A	Other N/A

Protective Gloves As required for hot materials

Other Protective Clothing or Equipment N/A

Work/Hygienic Practices N/A