

# **B** BROOKWOOD LAMINATING

## Material Safety Data Sheet

Identity:  
Weathermax

### Section I

Manufacturer's Name  
**Brookwood Laminating**

Telephone Number for Information  
**860-774-5001**

Address  
**275 Putnam Road  
PO Box 176  
Waregan, CT 06387**

Date Prepared  
**02/11/09**

### Section II – Hazardous Ingredients/Identity Information

This product contains no hazardous ingredients as defined under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

### Section III – Physical/Chemical Characteristics

Boiling Point

**Not established**

Viscosity

**Not established**

Vapor Pressure

**Not established**

Vapor Density

**Not established**

Solubility in water

**Insoluble**

Appearance and Odor

**Fabric color**

Melting Point

**Not established**

### Section IV – Fire and Explosion Hazard Data

Flash Point (Method)

**Not established**

Flammable Limits

**Not established**

Extinguishing Media

**Dry chemical, water spray, foam or carbon dioxide**

Hazardous Thermal Decomposition Products

**Inhalation of fumes from overheating may cause polymer fume fever, a temporary flu-like illness with fever, chills and sometimes cough, of approximately 24 hour duration. Heating above 750°F can evolve hydrogen fluoride and carbonyl fluoride. Inhalation of low concentration of hydrogen fluoride can initially include symptoms of choking, coughing and severe eye, nose and throat irritation, possibly followed after a symptomless period of one or two days by fever, chills, difficulty breathing or shortness of breath.**

# **B** BROOKWOOD LAMINATING

## Special Fire Fighting Procedures

Difficult to ignite, and flame goes out when ignition source is removed (UL-94). Limited flame spread and low smoke generation (NFPA 262-1990, UL-910). Complies with NFPA definition of "limited combustible" material. High self-ignition and auto-ignition temperatures (ASTM D1929). Firefighters should wear self-contained breathing apparatus. Wear full protective equipment. Hydrogen fluoride fumes emitted during a fire can react with water to form hydrofluoric acid. Wear neoprene gloves when handling refuse from fire.

Unusual Fire and Explosion Hazards  
**None known**

## Section V – Reactivity Data

Stability

**Stable**

Conditions to Avoid

**Temperatures above 570°F**

Materials to Avoid

**Strong Oxidizing Agents  
and finely divided metal powders**

Hazardous Polymerization

## Section VI – Health Hazard Data

Inhalation

**Not expected to pose an inhalation hazard**

Eye Contact

**Not expected to pose an eye hazard**

Skin Contact

**Not expected to pose a skin hazard**

Ingestion

**Not expected to pose an ingestion hazard**

## Section VII – Precautions for Safe Handling and Use

Waste Disposal

**The fabric should not require disposal as a hazardous waste under the federal Resource Conservation and Recovery Act (RCRA). Incinerate only if incinerator is capable of scrubbing out hydrogen fluoride and other acidic combustion products. While no special waste considerations should apply, the user should consult with regulatory authorities in the appropriate jurisdiction to determine applicable Federal, State and Local disposal requirements.**

Precautions to be taken in Handling and Storage

**This product is a fabric material. No special precautions are necessary. Where large quantities of material are stored, general ventilation should be adequate**

# B BROOKWOOD LAMINATING

## Section VIII – Control Measure

Respiratory Protection  
**Not required**

Ventilation  
**Not required**

Eye Protection  
**Not required**

Protective Gloves  
**Not required**

Exposure Limits  
**Not established**


## Section IX – Additional Precautions or Comments

This material safety data sheet has been prepared by Brookwood Laminating to characterize the potential physical hazards and health hazards of the product described herein. Brookwood Laminating offers no warranty with respect to the accuracy or completeness of the information provided.

Please contact Brookwood Laminating's Environmental, Health and Safety Office at the phone number provided below if you have questions regarding the information provided or require additional assistance.

Environmental, Health and Safety Manager  
Brookwood Laminating  
275 Putnam Road  
PO Box 176  
Wauregan, CT 06387

Telephone: 860-774-5001



**Material Safety Data Sheet**

Identity:  
Weathermax

**Section I**

Manufacturer's Name  
**Brookwood Laminating**

Telephone Number for Information  
**860-774-5001**

Address  
**275 Putnam Road  
PO Box 176  
Wauregan, CT 06387**

Date Prepared  
**02/11/09**

**Section II – Hazardous Ingredients/Identity Information**

This product contains no hazardous ingredients as defined under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

**Section III – Physical/Chemical Characteristics**

Boiling Point  
**Not established**

Viscosity  
**Not established**

Vapor Pressure  
**Not established**

Vapor Density  
**Not established**

Solubility in water  
**Insoluble**

Appearance and Odor  
**Fabric color**

**Section IV – Fire and Explosion Hazard Data**

Flash Point (Method)  
**Not established**

Flammable Limits  
**Not established**

Extinguishing Media

**Dry chemical, water spray, foam or carbon dioxide**

Hazardous Thermal Decomposition Products

**Inhalation of fumes from overheating may cause polymer fume fever, a temporary flu-like illness with fever, chills and sometimes cough, of approximately 24 hour duration. Heating above 750°F can evolve hydrogen fluoride and carbonyl fluoride. Inhalation of low concentration of hydrogen fluoride can initially include symptoms of choking, coughing and severe eye, nose and throat irritation, possibly followed after a symptomless period of one or two days by fever, chills, difficulty breathing or shortness of breath.**

# **B** BROOKWOOD LAMINATING

## Special Fire Fighting Procedures

**Difficult to ignite, and flame goes out when ignition source is removed (UL-94). Limited flame spread and low smoke generation (NFPA 262-1990, UL-910).**

**Complies with NFPA definition of "limited combustible" material. High self-ignition and auto-ignition temperatures (ASTM D1929).**

**Firefighters should wear self-contained breathing apparatus. Wear full protective equipment. Hydrogen fluoride fumes emitted during a fire can react with water to form hydrofluoric acid. Wear neoprene gloves when handling refuse from fire.**

Unusual Fire and Explosion Hazards  
**None known**

## Section V – Reactivity Data

Stability  
**Stable**

Conditions to Avoid  
**Temperatures above 570°F**

Materials to Avoid

**Strong Oxidizing Agents and finely divided metal powders**

Hazardous Polymerization

## Section VI – Health Hazard Data

Inhalation

**Not expected to pose an inhalation hazard**

Eye Contact

**Not expected to pose an eye hazard**

Skin Contact

**Not expected to pose a skin hazard**

Ingestion

**Not expected to pose an ingestion hazard**

## Section VII – Precautions for Safe Handling and Use

Waste Disposal

**The fabric should not require disposal as a hazardous waste under the federal Resource Conservation and Recovery Act (RCRA). Incinerate only if incinerator is capable of scrubbing out hydrogen fluoride and other acidic combustion products. While no special waste considerations should apply, the user should consult with regulatory authorities in the appropriate jurisdiction to determine applicable Federal, State and Local disposal requirements.**

Precautions to be taken in Handling and Storage

**This product is a fabric material. No special precautions are necessary. Where large quantities of material are stored, general ventilation should be adequate**



**BROOKWOOD LAMINATING**

**Section VIII – Control Measure**

Respiratory Protection  
**Not required**

Ventilation  
**Not required**

Eye Protection  
**Not required**

Protective Gloves  
**Not required**

Exposure Limits  
**Not established**

**Section IX – Additional Precautions or Comments**

This material safety data sheet has been prepared by Brookwood Laminating to characterize the potential physical hazards and health hazards of the product described herein. Brookwood Laminating offers no warranty with respect to the accuracy or completeness of the information provided.

Please contact Brookwood Laminating's Environmental, Health and Safety Office at the phone number provided below if you have questions regarding the information provided or require additional assistance.

Environmental, Health and Safety Manager  
Brookwood Laminating  
275 Putnam Road  
PO Box 176  
Wauregan, CT 06387

Telephone: 860-774-5001



## MATERIAL SAFETY DATA SHEET

### DYED, PRINTED, COATED AND/OR FINISHED TEXTILE FABRICS

September 1, 2008

Page 2 of 3

#### Section 5: FIRE FIGHTING MEASURES

**NFPA/HMIS Rating:** Health 0 Fire 0 Reactivity 0  
(0)- least, (1)- slight, (2)- moderate, (3)- high, (4)- extreme

**EXTINGUISHING MEDIA:** Foam X Water Spray X CO<sub>2</sub> X

**Special Fire Fighting Procedures:** Firefighters should wear full protective equipment commensurate with the conditions of the fire.

**Unusual Fire & Explosion Hazards:** None known. This material will melt or burn in a fire as would nylon or polyester fabrics and emit hazardous by-products associated with the burning of such fabrics.

#### Section 6: ACCIDENTAL RELEASE MEASURES

**If Material Is Spilled:** The product is a fabric material. No spill precautions are necessary.

#### Section 7: HANDLING & STORAGE

**Handling:** The product is a fabric material. No special precautions are necessary.

**Storage:** No special precautions are necessary. Where large quantities of material are stored, general ventilation should be adequate.

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

The product is a fabric material. No special precautions are necessary. Where large quantities of material are stored, general ventilation should be adequate.

#### Section 9: PHYSICAL & CHEMICAL PROPERTIES

**Specific Gravity:** Not determined. **Solubility in Water:** Not applicable. **pH:** Not applicable.

#### Section 10: STABILITY & REACTIVITY

**Stability:** Material is stable. **Incompatibility:** Not determined.

**Hazardous Decomposition Products:** Carbon dioxide, carbon monoxide

**Hazardous Polymerization:** Will not occur.

#### Section 11: TOXICOLOGICAL INFORMATION

**Toxicity Data:** No information available.

**Positive Teratogen/Mutagen/Carcinogen (NTP):** No. **Potential Carcinogen OSHA/IARC:** No.